



Europäisches
Patentamt

European
Patent Office

PCT/NL

10/535750
03/00818
Rec'd PCT/PTO 23 MAY 2005
Office européen
des brevets

Bescheinigung

Certificate

Attestation

REC'D 03 FEB 2004

WIPO

PCT

Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

02079845.0

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

BEST AVAILABLE COPY



Anmeldung Nr:
Application no.: 02079845.0
Demande no:

Anmeldetag:
Date of filing: 20.11.02
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Wageningen University
P.O. Box 9101
6700 HB Wageningen
PAYS-BAS
Paques B.V.
P.O. Box 52
T. de Boerstraat 11-13
NL-8560 AB Balk
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

Process for anaerobic oxidation of methane

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

C12P/

Am Anmeldetag benannte Vertragstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR IE IT LI LU MC NL PT SE SK TR

Process for Anaerobic Oxidation of Methane

Field of the invention

The present invention relates to an oxygen-free biological process for converting methane to hydrogen or hydrogen equivalents. Furthermore, the invention relates to a biological process of reducing sulphur compounds to sulphide.

Background

Biological methane oxidation in the presence of oxygen is a well-established process in natural habitats and in industrial applications. However, no pure or defined microbial cultures are known that are capable of anaerobic methane oxidation (Orphan et al., *Proc. Natl. Acad. Sci. USA* (2002), **99**, 7663-7668). Hence, anaerobic oxidation of methane is not well-understood and is not applied on an industrial scale.

Removal of sulphur oxide compounds such as sulphate, sulphite, sulphur dioxide, thiosulphate and the like and elemental sulphur by anaerobic conversion to sulphide at moderate or high temperature is well known, e.g. from EP-A-0451922, WO 92/17410, WO 93/24416 and WO 98/02524. These processes usually require an electron donor (or hydrogen donor) which can be hydrogen, carbon monoxide or organic molecules such as alcohols and fatty acids.

It was found recently (Balk et al., *Int. J. Syst. Evol. Microbiol.* (2002), **52**, 1361-1368) that certain *Thermotoga* species are capable of anaerobically degrading methanol, alone, in coculture with *Methanothermobacter* or *Thermodesulfovibrio* species, or in the presence of sulphur, sulphur oxide compounds or organic sulphur compounds, such as anthraquinone-2,6-disulphonate.

Summary of the invention

It was found according to the invention that anaerobic thermophilic bacteria of the order of the *Thermotogales*, especially from the species *Thermotoga*, are capable of converting methane, in the absence of oxygen, to hydrogen or hydrogen equivalents. The hydrogen produced can be used as such, or can be used to provide hydrogen equivalents suitable for reducing various compounds e.g. sulphur compounds such as sulphate, sulphite and thiosulphate. It was furthermore found that hydrogen equivalents (electron donors) required for biological reduction reactions can be effectively provided by methane oxidation by anaerobic methane-oxidising bacteria. Thus the invention concerns a process of producing hydrogen or hydrogen equivalents by anaerobically subjecting methane to the activity of a *Thermotogales* species or strain. Similarly, the

invention concerns a process of anaerobic oxidising methane using a *Thermotogales* species or strain. Furthermore, the invention concerns a process for biological reduction of chemicals such as sulphur compounds and metals, wherein the hydrogen equivalents are produced by subjecting methane to anaerobic methane-oxidising bacteria.

5 *Description of the invention*


The invention pertains to the anaerobic, bacterial production of hydrogen or hydrogen equivalents. In the present context, hydrogen equivalents are understood to comprise atoms, molecules or electrons, i.e. reduction equivalents, which lower the oxidation state of a substrate. They are also referred to as electron donors. Where the
10 present process produces hydrogen equivalents, as distinct from (molecular) hydrogen, the process is carried out in the presence of a suitable substrate capable of accepting the hydrogen equivalents. Where reference is made to methane, also higher alkanes and alkenes, such as ethane, ethene propane, etc. are contemplated.

The bacteria to be used according to the invention are anaerobic methane-
15 oxidising (alkane-oxidising) bacteria. These bacteria include terrestrial and aquatic (marine) species, which can be obtained from hydrothermal sources, oil-wells, and sometimes anaerobic thermophilic bioreactors. They can grow under a variety of environmental conditions and, depending on the natural source and possibly adaptation processes, they can be mesophilic or thermophilic. Examples of suitable bacteria belong
20 to the order of the *Thermotogales*, which are mostly thermophilic. A description thereof is given by Wery et al. (*FEMS Microbiol. Biol.* 41, (2002) 105-114) and Reysenbach et al. (*Int. J. Syst. Evol. Microbiol.*, 52, (2002) 685-690). The *Thermotogales* include the genera *Marinitoga*, *Geotoga*, *Petrotoga*, *Thermotoga*, *Thermosipho* and *Fervido-*
bacterium. They are especially from the group containing the latter three genera. These
25 include the species (with DSM accession numbers) *Thermotoga maritima* (DSM 3109), *Thermotoga thermarum* (DSM 5069), *Thermotoga hypogea* (DSM 11164), *Thermotoga subterranea* (DSM 9912), *Thermotoga elffi* (DSM 9442), *Thermotoga lettingae* (DSM 14385), *Thermosipho melanesiensis* (DSM 12029), *Thermosipho geolei* (DSM 13256), *Fervidobacterium islandicum* (DSM 5733) and *F. nodosum* (DSM 5306). Most of them
30 are available in recognised culture collection such as DSM or ATCC, and the genome of some of them, such as *Thermotoga maritima*, has been sequenced (Nelson et al., *Nature* (1999), 399, 323-329).

The methane-oxidising bacteria may be used as a pure culture of one of the species or strains mentioned above or as a defined mixture with other bacteria, or as a part of a mixed culture obtained from environmental samples or from bioreactors, if necessary and preferably after adaptation to the desired process conditions. The use of a
5 pure culture has the advantage of allowing the process to be controlled as desired. The invention also concerns such pure cultures as well as defined combinations of cultures as further illustrated below.

The species to be used in the process of the invention are mesophilic or thermophilic species. The thermophilic species have their maximum activity between 50
10 and 100°C, but they are generally sufficiently active for the process to be carried out at temperatures between 30 and 50°C as well. Mesophilic species have their maximum activity between 30 and 50°C, but are sufficiently active from 25°C and up to e.g. 60°C. The most preferred temperatures for the process of the invention are between 30 and 90°C.

15 In an embodiment of the process of the invention, the anaerobic methane oxidation is performed for producing molecular hydrogen. The relevant total reaction can be simplified as follows:



The culture medium contains basic mineral medium supplemented with growth factors
20 into which methane is introduced e.g. by sparging or another method that ensures intimate contact with the micro-organisms. The hydrogen produced can be collected e.g. using gas recirculation, wherein the gas is contacted with a selective membrane which is permeable for hydrogen and impermeable for larger molecules including methane, and the remaining gas can be recirculated to the methane-oxidising reactor. Alternatively,
25 suitable selective absorbents can be arranged in such a manner that the gas evolving from the reactor is contacted with the absorbents. Efficient withdrawal of hydrogen from the reaction mixture ensures sufficient bioconversion of methane to hydrogen. The hydrogen produced can be used as a fuel or as a chemical synthesis agent or in biological or chemical reduction processes.

30 In a preferred embodiment, the anaerobic methane oxidation is performed for reducing substrates, such as nitrate, azo compounds, inorganic and organic sulphur compounds such as elemental sulphur, thiosulphate, polysulphides, anthraquinone-2,6-disulphonate, metals, oxidised halogen compounds, nitrate and other compounds that

must be removed. The compounds can be present in liquid waste streams, if appropriate after extraction from gas stream by scrubbing or the like. They can also be present e.g. as soil contaminants. The compounds to be reduced can also be present in production lines, for producing desired reduced compounds. The following reaction may apply:



wherein A is a hydrogen acceptor, and AH₂ may be replaced by equivalents or subsequent conversion products. According to this embodiment, methane-oxidising bacteria to be used include those of the *Thermotogales* order as described above, as well as other methane-oxidisers, e.g. those related to *Desulfosarcina*. The reduction step
10 itself is in particular a biological reduction using suitable reducing organisms. This process is schematically illustrated in figure 1.

In a particularly preferred embodiment, the anaerobic methane oxidation is used to reduce oxidised sulphur compounds, such as sulphate, sulphite and elemental sulphur. In the following, reference is made to sulphate, but other sulphur-oxygen species, such
15 as sulphite and hydrogenated (e.g. bisulphite) and neutral (e.g. sulphur trioxide) equivalents are also comprised. The relevant total reaction can be simplified as follows:



This embodiment requires the presence of agents capable of transferring hydrogen equivalents to sulphate. Such agents are especially sulphate-reducing micro-organisms,
20 which are known in the art. Suitable sulphate-reducing micro-organisms include mesophilic and thermophilic hydrogen-utilising strains from the bacterial sulphate-reducing genera, e.g. *Desulfomonas*, *Desulfovibrio*, *Thermodesulfovibrio* and *Desulfotomaculum* (e.g. the strain described in WO 98/02524) as well as the archaeal sulphate-reducing genus, e.g. *Archaeoglobus*, such as *A. profundus*.

25 The conversion of sulphate by a coculture comprising the anaerobic methane oxidisers as described above can be carried out in a conventional bioreactor having an inlet for sulphate-containing water, e.g. originating from a gas desulphurisation plant, a gas inlet for methane supply, a liquid outlet for sulphide-containing water, a gas outlet for the resulting gas mixture containing e.g. residual methane, hydrogen, hydrogen
30 sulphide, and optionally means for supporting the biomass and for keeping it in effective contact with the liquid and (dissolved) gaseous materials, optional filters for separating gaseous products from the culture mixture and means for maintaining the desired reactor temperature. Furthermore, a gas separation unit may be provided for separating the resulting gas mixture and returning recovered methane as well a

treatment unit for treating hydrogen sulphide, e.g. a unit for biologically converting sulphide to elemental sulphur and for separating off the sulphur. In addition to methane, further electron donors, e.g. methanol or other organic matter may be supplied to the bioreactor.

5 Variations in the process of reducing sulphur compounds using a coculture of methane-oxidisers and sulphate-reducers are schematically illustrated in Figures 2-5. Fig. 2 is a flow diagram for reducing sulphate to sulphide, followed by biological oxidation of sulphide to elemental sulphur. Fig. shows sulphate reduction in combination with metal precipitation in the form of metal sulphides (MeS) by the
10 hydrogen sulphide produced and oxidation of the surplus hydrogen sulphide to elemental sulphur. Fig. 4 shows two variants of a process for producing hydrogen sulphide, either by separate stripping, or by hydrogen sulphide removal using the methane stream. The hydrogen sulphide can be concentrated and used for sulphuric acid production. Fig. 5 illustrates sulphur dioxide removal from gases by scrubbing (first
15 stage) followed by biological reduction as in figure 2.

In another embodiment of the process of the invention can be used for reducing noxious bromate or chlorate to less noxious bromide and chloride. These compounds can be present in process water from chemical industries. The reduction of bromate or chlorate requires the presence of bromate or chlorate reducing species, which can be
20 sulphate reducing bacteria and archaea. Similarly, nitrate reduction can be performed using commonly known denitrifiers.

According to a further embodiment, the process may be used for reducing metal ions to their low-valence or zero-valence state. They can be precipitated and separated in these lower valence states e.g. as oxides, hydroxides, carbonates, phosphates,
25 sulphides or neutral metals. The biological reduction of metals is described for example in WO 00/39035. Examples of metals that can be reduced and converted to insoluble metals or insoluble metal oxides, hydroxides or the like include selenium, tellurium, uranium, molybdenum, vanadium, chromium, and manganese. Bacteria capable of reducing these metals include the genera *Geobacter*, *Pseudomonas*, *Shewanella*,
30 *Desulfovibrio*, *Desulfobacterium*, *Desulfomicrobium*, *Desulforomonas* and *Alteromonas*. If desired, a moving sand filter can be used for separating the resulting metal precipitates as described in WO 00/39035.

The use of the methane-oxidising bacteria in providing reducing equivalents in (biological) reduction processes is beneficial in technical and economical terms. Current

process using methane as the ultimate reducing agent require the intermediary use of hydrogen to be produced from methane by chemical (catalytic) reforming. This implies the investment in and use of reformers or similar equipment and also consumes about 50% of the methane by combustion needed to keep the catalytic process at the necessary high temperature. These drawbacks are eliminated by the present biological process, thus resulting in substantial cost savings both in equipment cost, and in operational cost (e.g. 50% lower methane consumption).

The process of the invention can be carried out in a conventional bioreactor of the anaerobic type, having means for introducing a gas into the reactor contents and means for carrying off gases from the headspace of the reactor. The reactor can be of the stirred type, but preferably the reactor is of a type having biofilms, present on carrier particles such as sand, basalt, polymer particles etc., or in the form of granules, plates, membranes and the like, in order to optimise contact between the substrate (methane) and the micro-organisms, and – in case of coculture – between the different micro-organisms. An example of a suitable reactor type is the so-called gaslift-loop reactor, which is operated using a vertical circulation activated by the gas (methane) introduced at the bottom of the reactor.

The process of the invention can be carried out at atmospheric pressure, or - if desired - at elevated pressure, e.g. pressure in the of 10-100 bar, using appropriate pressure-resistant equipment. Elevated pressures may have the advantage of increasing the conversion rate of the biological processes using methane.

Examples

Strains. *Thermotoga maritima* (DSM 3109) and *Archaeoglobus profundus* (DSM 5631) were purchased from the Deutsche Sammlung von Mikroorganismen und Zellkulturen (Braunschweig, Germany). *T. lettingae* (DSM 14385) and *Desulfotomaculum* sp. strain WW1 were isolated in our laboratory.

Cultivation techniques. The cells were grown in an anaerobic medium supplemented with 0.15 g/l yeast extract. The medium contained (per liter) 0.335 g of KCl, 4.0 g of $MgCl_2 \cdot 6H_2O$, 3.45 g of $MgSO_4 \cdot 7H_2O$, 0.25 g of NH_4Cl , 10 g of NaCl, 0.10 g of K_2HPO_4 , 5.0 g of $NaHCO_3$, 0.5 g of $Na_2S \cdot 9H_2O$, 1.0 g of Na_2SO_4 , 10 ml of trace element and 10 ml vitamin solutions which were based on medium 141 of DSM (<http://www.dsmz.de>), 1000 ml of demineralised water. $NaHCO_3$, Na_2S , and vitamin solution were added after sterilisation. The medium was boiled and cooled to room

temperature under a stream of O₂-free N₂ gas. The medium was anaerobically dispensed into serum bottles and a gas phase of 180 kPa N₂/CO₂ (80/20, v/v) was applied. The bottles were closed with butyl rubber stoppers and sealed with crimp seals. The medium was autoclaved for 20 min at 121°C.

- 5 For coculture experiments, *A. profundus* and *Desulfotomaculum* sp. strain WW1 were grown on H₂ and CO₂ in 248 ml serum vials with 50 ml medium at 80°C and 65°C, respectively. As additional carbon source, 1 mM of sodium acetate was added. The sulphate reducers were grown for 1 day and then the gas phase was changed to 180 kPa N₂/CO₂ (80/20, v/v) and CH₄ gas was added to the final concentration of 1.75 mmol per vial. The *A. profundus* culture was inoculated with *T. maritima* and the *Desulfotomaculum* sp. with *T. lettingae*. For inoculation, methane adapted cultures of *T. maritima* and *T. lettingae* were used. Since the medium already contained nearly 1 mmol of sulphate per vial, no sulphate was added.

- Analytical techniques.* Highly pure (min 99% ¹³C) methane gas was obtained from 15 Campro Scientific B.V. (Veenendaal, NL). Serum vials were prepared with approximately 1.75 mmol of ¹³C-methane as substrate in 50 ml medium. Control bottles were prepared with or without ¹³C-methane, thiosulphate and organisms. NMR-tubes contained the sample, 10% (v/v) D₂O and 100 mM dioxane to give a final volume of 15 ml. The proton-decoupled ¹³C-NMR-spectra of the samples were recorded at 75.47 20 MHz on a Bruker AMX-300 NMR spectrometer. For each spectrum 7200 transients (5 h) were accumulated and stored on disc using 32k data points, a 45° pulse angle and a delay time of 1 s between pulses. The measuring temperature was maintained at 10°C and the chemical shift belonging to the dioxane carbon nuclei (67.4 ppm) was used as an internal standard. The deuterium in the samples (10%, v/v) was used for field lock 25 and dioxane as an internal standard.

- Hydrogen and methane were determined at room temperature by either gas chromatography (GC) (see: Stams et al. *Appl. Environ. Microbiol.* (1993) 59 114-1119) or GC (Hewlett Packard model 5890) equipped with a mass selective detector (MS). Methane, carbon dioxide and their stable isotopes were separated on a capillary column 30 (innowax, 30 m x 0.25 mm (df=0.5 µm), Packard, NL) with helium as the carrier gas. Gas samples (200 µl) were injected in a split injector (inlet pressure 1 kPa; split ratio 25:1) at a column temperature of 35°C. Methane and carbon dioxide and their stable isotopes were monitored at *m/z* 16 and 17, and 44 and 45, respectively. Total methane

and CO₂ concentrations were determined quantitatively by gas chromatography (see Stams et al. (1993 *above*). The H¹³CO₃⁻ concentration in the liquid phase was calculated from the amount of CO₂ which accumulated in the gas phase after acidification. Thiosulphate and sulphate were analysed by HPLC (see: Scholten and Stams, *Anthonie van Leeuwenhoek* (1995) 68, 309-315). Sulphide was determined as described by Trüper and Schlegel (see: *Anthonie van Leeuwenhoek* (1964) 30, 225-238).

Example 1. Anaerobic methane oxidation by *Thermotoga* species

Thermotoga maritima and *T. lettingae* were incubated with highly pure ¹³C-labelled methane under strictly anaerobic conditions in the presence of thiosulphate as the electron acceptor. The experiments were carried out was studied in duplicate cultures at incubation temperatures of 80°C and 65°C, respectively. Methane oxidation and product formation were determined by analysing the gas phase by gas chromatography (GC) and GC-mass spectroscopy (MS) and by using Nuclear Magnetic Resonance spectroscopy (NMR) for liquid samples.

In acidified samples, the total CO₂ which accumulated in the gas phase after 40 days of incubation was measured by using GC (Table 1). In the control incubation without methane which contained totally 4.87 mmol of CO₂ per vial, slight growth was observed due to the presence of yeast extract in the medium and consequently, unlabelled CO₂ was found. Growth in the presence of ¹³C-methane and thiosulphate by *T. maritima* and *T. lettingae* resulted in significantly increased cell numbers (Table 1). The stoichiometry of methane conversion by the two cultures yielded nearly equal amounts of products after 40 days of incubation. The percentage of ¹³C in CO₂ was 5.9 % in liquid phase and 2.1 % in gas phase for *T. lettingae*. These values for *T. maritima* were 6.2% and 2.4%, respectively. The ratio of methane oxidation to carbon dioxide and thiosulphate reduction to sulphide in both samples were approximately 1:1 and 1:2, respectively. Nearly 1 mmol of ¹³C-methane per vial was utilised by both bacteria. The rest of the methane in the vials was not utilised even after 40 days of prolonged incubations. However, when less methane was added (up to 0.5 mmol per vial), all ¹³C-methane was completely utilised by the two bacteria. In both cases, measurable methane conversion started after around 10 days. The rates of anaerobic methane transformation by *T. maritima* and *T. lettingae* were 32 and 30 µmol per vial per day, respectively. The ¹³C-carbon recoveries for *T. maritima* and *T. lettingae* were calculated to be 82% and 79%, respectively.

Table 1 a. ^{13}C -methane oxidation in the presence of thiosulphate by *T. maritima*†.

	$^{13}\text{CH}_4$	Thio-sulphate	Total CO_2^*	Total Sulphide #	Hydro-gen	Number of cells (ml)†
Day 0	1.75	0.99	4.87	0.05	0.00	4×10^5
Day 40	0.68	0.00	5.75	1.96	0.05	8×10^7
Utilised/produced	1.07	0.99	0.88	1.91	0.05	

Table 1. b. ^{13}C -methane oxidation in the presence of thiosulphate by *T. lettingae*‡.

	$^{13}\text{CH}_4$	Thio-sulphate	Total CO_2^*	Total Sulphide #	Hydro-gen	Number of cells (ml)†
Day 0	1.75	1.01	4.87	0.05	0.00	5×10^5
Day 40	0.71	0.00	5.68	1.89	0.04	1×10^7
Utilized/produced	1.05	1.01	0.81	1.84	0.04	

‡; The values were calculated in mmol per vial and corrected with the control samples. All measurements were done in duplicates and the highest values of each sample were calculated

5 *; Total CO_2 includes CO_2 from the medium composition in liquid and gas phases and ^{13}C -carbon dioxide formed

#; Total sulphide includes sulphide from the medium composition in liquid and gas phases and sulphide formed during methane oxidation

†; Ballooning cells were not taken into account during counting of the cells

10 Example 2: Sulphate reduction by coculture with *Thermotoga* species

Coculture experiments were performed by growing *Archaeoglobus profundus* with *T. maritima* at 80°C and *Desulfotomaculum* sp. strain WW1 with *T. lettingae* at 65°C (Table 2). In both cases, sulphate was utilised as the electron acceptor. The ratio of CO_2 formation from methane and sulphate conversion to sulphide were nearly 1:1 for both
 15 cocultures. The calculated rates of methane conversion were slower than in the case with thiosulphate, which was about $20 \mu\text{mol}$ per vial per day. Conversion of methane coupled to sulphate reduction led to more than ten-fold increased cell numbers of both the *Thermotoga* species and the sulphate-reducing microorganisms. The ^{13}C -carbon recoveries for the cocultures of *T. maritima* and *T. lettingae* were calculated to be 85%
 20 and 78%, respectively.

Table 2a. ^{13}C -methane oxidation by *T. maritima* (T.m.) in coculture with *Archaeoglobus profundus* (A.p.) in the presence of sulphate†.

	$^{13}\text{CH}_4$	Total Sulphate	Total CO_2^*	Total Sulphide #	Number of cells (ml)†
Day 0	1.75	1.10	4.87	0.11	3×10^5 (T.m.) 2×10^6 (A.p.)
Day 40	1.07	0.31	5.53	0.85	5×10^7 (T.m.) 7×10^8 (A.p.)
Utilised/produced	0.68	0.79	0.57	0.74	

Table 2b. ^{13}C -methane oxidation by *T. lettingae* (T.l.) in coculture with *Desulfotomaculum* sp. strain WW1 (WW1) in the presence of sulphate†.

	$^{13}\text{CH}_4$	Total Sulphate	Total CO_2^*	Total Sulphide #	Number of cells (ml) †
Day 0	1.75	1.10	4.87	0.07	4×10^5 (T.l.) 3×10^6 (WW1)
Day 40	1.21	0.50	5.28	0.53	2×10^7 (T.l.) 8×10^8 (WW1)
Utilised/produced	0.54	0.60	0.41	0.51	

5 For symbols see Table 1.

Previous results showed that *T. maritima* and *T. lettingae* are able to grow on other C_1 -compounds like $\text{H}_2\text{-CO}_2$, formate, methanol, and methylamine in the presence thiosulphate and yeast extract¹⁸. We also observed that addition of 0.5 to 5.0 g/l of yeast extract resulted in better growth and consequently slightly faster methane oxidation than in the original medium. In the absence of yeast extract, the pure cultures could not grow, even not on glucose. The rate of methane utilisation could be increased from 32 to 33 μmol per vial per day for *T. maritima* and from 30 to 31 μmol per vial for *T. lettingae* when 2.5 g/l yeast extract was added in the medium. However, similarly to the findings within original medium which contained 0.15 g/l of yeast extract, methane oxidation started only after around 10 days of incubation. When more than 5.0 g/l of yeast extract was added, growth for both organisms was better but methane oxidation rates were not higher than the obtained values.

Claims

1. A process for converting methane to produce hydrogen or hydrogen equivalents, *characterised* in that methane is subjected anaerobically to the activity of methane-oxidising species.
2. A process according to claim 1, wherein the methane-oxidising species is a *Thermotogales* species, in particular a *Thermotoga* species.
3. A process according to claim 2, wherein the *Thermotoga* species comprises *T. maritima* or *T. lettingae*.
4. A process according to any one of claims 1-3, which is carried out at a temperature between 50 and 100°C.
5. A process according to any one of claims 1-4, which is carried out in the presence of thiosulphate.
6. A process for reducing chemical compounds by biological reduction using hydrogen equivalents, *characterised* in that the hydrogen equivalents are produced by subjecting methane to anaerobic methane-oxidising bacteria.
7. A process according to claim 6, wherein sulphur compounds are reduced to sulphide using a sulphate-reducing species.
8. A process according to claim 7, wherein the sulphur compounds comprise sulphate and/or sulphite.
9. A process according to claim 7 or 8, wherein the anaerobic methane-oxidising species comprises a *Thermotoga*, *Thermosipho* or *Fervidobacterium* species.
10. A process according to claim 7 or 8, wherein the sulphate-reducing species comprises an *Archaeoglobus*, *Desulfotomaculum*, *Desulforomonas*, *Desulfovibrio* or *Thermodesulfovibrio* species.
11. A process according to claim 6, wherein metals are reduced from a high valence state to a low-valence or zero-valence state.

12. A process according to any one of claims 6-11, wherein a temperature of between 25 and 90°C is used.
13. A mixed culture use, containing one or more anaerobic methane-oxidising species, in particular a *Thermotogales* species, and one or more sulphate-reducing or metal reducing species, in particular a *Archaeoglobus*, *Desulfotomaculum*, *Desulforomonas*, *Desulfovibrio* or *Thermodesulfovibrio* species.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record.**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.